SINCE 1972

POWERLIFT DUMBWAITERS CORPORATION www.dumbwaiters.com Job Name:	THE SMAR? Dumbwaiter Mod Have you contacted you for safety requirements: Is the dumbwaiter going to the living space below What will the dumbwaiter How many times will the	r primarily be used for? _		SAPILER ~ 1
Contractor's Name, Phone #, & Email: Ship to address: Is the "Ship To" address a	a commercial location?	Yes No No		
Owners' Name & Phone #	ation is for warranty recor		not contact the owner.	MAKI VVAY
The finished floor to finished floor n Bottom floor to middle floor: The overall height of shaft:	Middle			VVAX IO
3. The finished shaft width and depth Shaft Width:4. Desired loading heights: (Usually 36	Shaft D	finished wall surface to fine of the finished wall surface to fine of the finished wall surface to fine of the finished wall surface to finished w	, 	
Bottom floor: No. 5. Use the diagram on the right to ma locations of your openings and man wall to mount the rail assembly to.		Top floor Rails Opening at top floor Opening at middle		
**For clarity, stand on the bottom floot the "Bottom Floor Opening" to promark the locations on the diagram. 6. While facing each opening which significantly be a dear board to be a 2.2 Left and the control of the c	roperly ** Opening at top floor	Shaft	Rails Opening at top floor Opening at	
will the door handle be on? Left or Bottom floor: Top floor:	middle floor —	Width	middle floor	r } ~
7. Desired voltage for dumbwaiter: ☐ Single Phase - ☐ 208 V ☐ 230 V ☐ Three Phase - ☐ 208 V ☐ 230 V		**Bottom Floor Ope Opening at top flood Opening at middle	oor	
8. Dumbwaiter cars come with a 3" Lip 9. Accessories / Special Instructions:		_	□ NO LIP	