

| Contractor's Name, Phone #, & Email: Ship to address: Is the "Ship To" address a commercial location? Yes No | Powerlift Dumbwaiters Corporation www.dumbwaiters.com | Dumbwaiter Mode Have you contacted your for safety requirements? Is the dumbwaiter going to but the safety space below | WAY TO BUSE. I: □ P-300 □ Note the dumbwaiter shaft? | $AD_{U_{M_2}}$ $AJ-500$ $AJ-5$ |
|--|---|--|---|--|
| Ship to address: Is the "Ship To" address a commercial location? Yes No | JOD Name | | | |
| Owners' Name & Phone # Owners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters. 1. The finished floor to finished floor measurement: 2. The overall height of shaft: (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: Shaft Width: Shaft Depth: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. **For clarity, stand on the bottom floor and face the "Bottom Floor Opening" to properly mark the locations on the diagram.** 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: Single Phase - 208 V 230 V (extra for MJ-500) Three Phase - 208 V 230 V 460 V No Lip requires a car gate. NO LIP | Contractor's Name, Phone #, & Email: | | | |
| Owners' Name & Phone # Owners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters. 1. The finished floor to finished floor measurement: 2. The overall height of shaft: (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: Shaft Width: Shaft Depth: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. **For clarity, stand on the bottom floor and face the "Bottom Floor Opening" to properly mark the locations on the diagram.** 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: Single Phase - 208 V 230 V (extra for MJ-500) Three Phase - 208 V 230 V 460 V No Lip requires a car gate. NO LIP | Ship to address: | es a commercial location? | Voc D No D | |
| Owners' Name & Phone # Dwners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters. 1. The finished floor to finished floor measurement: | | | | |
| Owners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters. 1. The finished floor to finished floor measurement: 2. The overall height of shaft: (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: Shaft Width: Shaft Depth: The desired loading height. bottom floor: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. "**For clarity, stand on the bottom floor and face the "Bottom Floor Opening" to properly mark the locations on the diagram.** 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: Single Phase - 208 V 230 V (extra for MJ-500) Three Phase - 208 V 230 V 460 V Dopening at top floor 8. Dumbwaiter cars come with a 3" Lip. No Lip requires a car gate. NO LIP | | | | |
| 1. The finished floor to finished floor measurement: (The overall height of shaft: (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: Shaft Width: Shaft Depth: Shaft Depth: Shaft Depth: Shaft Width: Shaft Width: Shaft Depth: Shaft Depth: Shaft Width: Shaft Width: Shaft Width: Shaft Depth: Shaft Depth: Shaft Shaft 4. The desired loading height. Shaft bettom floor: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. Shaft Sha | | | | |
| 2. The overall height of shaft: (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: Shaft Width: Shaft Depth: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. **For clarity, stand on the bottom floor and face the "Bottom Floor Opening" to properly mark the locations on the diagram.** 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: Single Phase - 208 V 230 V 460 V Dopening at top floor Three Phase - 208 V 230 V 460 V Opening at top floor Top Floor Opening at top floor Arabitation of the top floor opening to properly width **Bottom Floor Opening** Opening at top floor Opening at top floor **Bottom Floor Opening** Opening at top floor Opening at top floor Opening at top floor Opening at top floor | | Powerlift does not instal | l or service dumbwaiters. | |
| (The distance from the bottom floor to the ceiling of the top floor.) 3. The rough or finished width and depth of the shaft: | | | | |
| Shaft Width: Shaft Depth: Finished Shaft 4. The desired loading height. bottom floor: top floor: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. | The overall height of shaft: (The distance | ee from the bottom floor to the ce | eiling of the top floor.) | |
| Shaft Width: Shaft Depth: Finished Shaft 4. The desired loading height. bottom floor: top floor: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. | 3. The rough or finished width and | depth of the shaft: | Rou | gh Shaft |
| (Usually 36", this is the height above the floor where the dumbwaiter car will stop.) 5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. | - | · | | |
| openings and mark one wall to mount the rail assembly to. | | | | |
| the "Bottom Floor Opening" to properly mark the locations on the diagram.** 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: 7. Desired voltage for dumbwaiter: Single Phase - | 9 | • | | t top floor |
| 6. While facing each opening which side will the door handle be on? Left or Right Bottom floor: Top Floor: 7. Desired voltage for dumbwaiter: Width **Bottom Floor Opening** Opening at top floor Single Phase - 208 V 230 V 460 V 460 V Opening at top floor Opening at top floor Width **Bottom Floor Opening** Opening at top floor Opening | the "Bottom Floor Opening" | to properly ram.** | | |
| Bottom floor: Top Floor: 7. Desired voltage for dumbwaiter: Width Single Phase - | | h side will Right Opening at □ | Shaft tde | Opening at |
| □ Single Phase - □ 208 V □ 230 V (extra for MJ-500) Three Phase - □ 208 V □ 230 V □ 460 V □ Opening at top floor 8. Dumbwaiter cars come with a 3" Lip. □ 3" LIP No Lip requires a car gate. □ NO LIP | Bottom floor: Top Floor: | | | ιορ ποσι |
| ☐ Three Phase - ☐ 208 V ☐ 230 V ☐ 460 V ☐ Opening at top floor 8. Dumbwaiter cars come with a 3" Lip. ☐ 3" LIP No Lip requires a car gate. ☐ NO LIP | 3 | LO V (M 500) | | ** |
| No Lip requires a car gate. | ☐ Three Phase - ☐ 208 V ☐ 23 | | | |
| 9. Accessories / Special Instructions: | | · | | |
| | 9. Accessories / Special Instruction | ns: | | |
| | | | | |