

Joh	POWERLIFT DUMBWAITERS CORPORATION Www.dumbwaiters.com  Dumbwaiter Model:	A PITER -
	ntractor's Name, Phone #, & Email:	
Shi	p to address:	
	tallation address:	
	vners' Name & Phone #	
Ow	Owners' information is for warranty records only. Powerlift does not contact the owner.	
1.	Powerlift does not install or service dumbwaiters.  The finished floor to finished floor measurements:  Bottom floor to middle floor: Middle floor to top floor:	THE SMART WAY TO
_	·	
2.	The overall height of shaft: ( The distance from the bottom floor to the ceiling of the top floor.)	
	The rough or finished width and depth of the shaft:  Shaft Width: Shaft Depth: Finished Shaft	BUY
4.	Desired loading heights: ( Usually 36", this is the height above the floor where the dumbwaiter car will stop.)  Bottom floor: Top floor:	
5.	Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to.	DUMB
	**For clarity, stand on the bottom floor and face the "Bottom Floor Opening" Rails \( \begin{align*}  Top floor Opening at Openin	Dumbwaiter
6.	Desired voltage for dumbwaiter:	1
	□ 110 V □ 220 V Width	. ,
7.	Dumbwaiter cars come with a 3" Lip. ☐ 3" LIP  **Bottom Floor Opening**  ☐ Opening at top floor ☐ Opening at middle floor	THE
8.	Accessories / Special Instructions:	JHE SMA

POWERLIFT DUMBWAITERS